Defence Research and Recherche et développement
Development Canada pour la défense Canada

DEFENCE **R&D** DÉFENSE

ISAR Motion Compensation using the registration-restoration-fusion method

T. Thayaparan

Defence R&D Canada – Ottawa

Canada

ISAR Motion Compensation using the registration-restoration-fusion method

T. Thayaparan
Defence R&D Canada – Ottawa

Defence R&D Canada – Ottawa

Technical Memorandum

DRDC Ottawa TM 2006-131

June 2006

AQ F06-12-0328

Abstract

A new method is developed to perform target translational and rotational motion compensation for ISAR imaging. The method is based on a registration-restoration-fusion technique. This technique provides an efficient method to resolve the image smearing caused by the time-varying behavior of the target scattering centers and leads to a well-focused ISAR image. The basic idea is to use the nearest neighbor method to obtain control points and estimate motion parameters from two or more candidate images. The registration processes use these estimated motion parameters to remove both translational and rotational motion. The restoration process may be used to eliminate the blur that is induced by the registration process. Furthermore, the fusion of two registered images before or after restoration processing could be used to generate the focused ISAR image. This proposed method has been successfully applied to both experimental and simulated ISAR data.

Résumé

Une nouvelle méthode est élaborée pour effectuer la compensation du mouvement de translation et de rotation de la cible, aux fins de l'imagerie ISAR. Cette méthode est basée sur une technique de cadrage-restitution-fusion. Cette technique constitue une méthode efficace pour résoudre la bavure de l'image causée par le comportement variable dans le temps des zones de diffusion de la cible et donne lieu à une image ISAR bien focalisée. Le concept de base consiste à utiliser la méthode du voisin le plus proche pour obtenir des points de contrôle et à estimer les paramètres de mouvement à partir de deux ou plusieurs images candidates. Les processus de cadrage utilisent ces paramètres de mouvement estimés pour supprimer tant le mouvement de translation que le mouvement de rotation. Le processus de restitution peut être utilisé pour éliminer le flou introduit par le processus de cadrage. Finalement, la fusion de deux images cadrées, avant ou après le processus de restitution, pourrait être utilisée pour générer l'image ISAR focalisée. Cette méthode proposée a été appliquée avec succès à des données ISAR tant expérimentales que simulées.

This page intentionally left blank.

Executive summary

Inverse synthetic aperture radar (ISAR) imaging is an effective way to acquire high resolution images of targets of interest at long range and as such is an irreplaceable tool in the task of non-cooperative target recognition (NCTR) of both ships and aircraft. The Canadian Air Force is currently upgrading the fleet of CP-140 Aurora maritime patrol aircraft to possess NCTR through ISAR in order to increase the capability of the Canadian Forces in both sovereignty patrols of Canadian territory and the protection of the Canadian Patrol Frigates and allied ships operating abroad as a coalition. The United States Navy's equivalent aircraft, the P-3 Orion, currently possesses this capability. Therefore, effective ISAR imaging will have a real impact in the decision making process in future military operations involving both Canadian and American forces.

In real-world ISAR imaging scenarios, the target is often engaged in complicated manoeuvres that combine translational and rotational motion. Significant blurring can result in the ISAR image unless a good motion compensation method is implemented. Therefore, a motion compensation method to focus ISAR images is of paramount importance to military and intelligence operations.

In this report a new method is developed and proposed to perform target translational and rotational motion compensation for ISAR imaging. The method is based on a registration-restoration-fusion technique. The basic idea is to use the nearest neighbor method to obtain control points and estimate motion parameters from two or more candidate images. The registration processes use these estimated motion parameters to remove both translational and rotational motion. The restoration process may be used to eliminate the blur that is induced by the registration process. Furthermore, the fusion of two registered images before or after restoration processing could be used to generate the focused ISAR image. This proposed approach has been successfully applied to both experimental and simulated ISAR data. This report provides the preliminary ground work for this challenging field of research.

Results also show that if a target is moving smoothly, standard motion compensation generates a clear image of the target by using the conventional Fourier transform methods. However, when a target performs complex motion such as perturbed random motions, standard motion compensation is not sufficient to generate an acceptable image. In this case, the registration-restoration-fusion motion compensation method provides an efficient candidate to resolve the image smearing caused by the time-varying behavior and leads to a well-focused ISAR image. This study

also adds insight into the distortion mechanisms that affect the ISAR images of a target in motion.

Sommaire

L'imagerie du radar à synthèse d'ouverture inverse (ISAR) est une façon efficace d'acquérir des images à haute résolution de cibles d'intérêt à longue distance et comme telle est un outil irremplaçable dans la tâche de reconnaissance de cible non coopérative (NCTR) à la fois de navires et d'aéronefs. La Force aérienne du Canada est en train de mettre à niveau la flotte d'avions de patrouille maritime CP-140 Aurora en les dotant de la fonction NCTR au moyen de l'ISAR afin d'augmenter la capacité des Forces canadiennes tant dans les patrouilles de protection de la souveraineté du territoire canadien que dans la protection des frégates de patrouille canadiennes et des navires alliés faisant partie d'une coalition à l'étranger. L'aéronef équivalent de la marine américaine, le P-3 Orion, est déjà doté de cette capacité. Par conséquent, une imagerie ISAR efficace aura une forte incidence sur le processus de prise de décisions lors d'opérations militaires futures effectuées par des forces canadiennes et américaines.

Dans les scénarios d'imagerie ISAR en conditions réelles, la cible se trouve souvent à effectuer des manIJuvres complexes qui combinent le mouvement de translation et le mouvement de rotation. Un flou considérable peut se produire dans l'image ISAR, à moins qu'une bonne méthode de compensation du mouvement ne soit mise en IJuvre. Par conséquent, une méthode de compensation du mouvement permettant de focaliser les images ISAR est primordiale pour les opérations militaires et de renseignement.

Le présent rapport porte sur l'élaboration d'une nouvelle méthode proposée pour effectuer la compensation du mouvement de translation et de rotation de la cible, aux fins de l'imagerie ISAR. Cette méthode est basée sur une technique de cadrage-restitution-fusion. Le concept de base consiste à utiliser la méthode du voisin le plus proche pour obtenir des points de contrôle et à estimer les paramètres de mouvement à partir de deux ou plusieurs images candidates. Les processus de cadrage utilisent ces paramètres de mouvement estimés pour supprimer tant le mouvement de translation que le mouvement de rotation. Le processus de restitution peut être utilisé pour éliminer le flou introduit par le processus de cadrage. Finalement, la fusion de deux images cadrées, avant ou après le processus de restitution, pourrait être utilisée pour générer l'image ISAR focalisée. Cette méthode proposée a été appliquée avec succès à des données ISAR tant expérimentales que simulées. Le présent rapport jette les bases préliminaires de ce domaine de recherche riche en défis.

Les résultats montrent aussi que, si une cible se déplace uniformément, la compensation standard du mouvement génère une image claire de la cible en faisant appel aux méthodes de transformée de Fourier classiques. Cependant, lorsqu'une cible décrit des mouvements complexes, tels que des mouvements aléatoires perturbés, la compensation standard du mouvement ne suffit pas pour générer une image acceptable. Dans ce cas, la méthode de compensation du mouvement par cadrage-restitution-fusion constitue une option efficace pour résoudre la bavure de l'image causée par le comportement variable dans le temps et donne lieu à une image ISAR bien focalisée. De plus, la présente étude donne une meilleure idée des mécanismes de distorsion qui influent sur les images ISAR d'une cible en mouvement.

T. Thayaparan; 2006; ISAR Motion Compensation using the registration-restoration-fusion method; DRDC Ottawa TM 2006-131; R & D pour la défense Canada – Ottawa.

Table of contents

List of figures

List of tables

This page intentionally left blank.

1 Introduction

Inverse synthetic aperture radar (ISAR) imaging is an effective way to acquire high resolution images of targets of interest at long range and as such is an irreplaceable tool in the task of non-cooperative target recognition (NCTR) of both ships and aircraft [1-3]. In real-world ISAR imaging scenarios, the target is often engaged in complicated manoeuvres that combine translational and rotational motion. Significant blurring can result in the ISAR image [2-4], unless a good motion compensation method is implemented. Therefore, a motion compensation method to focus ISAR images is of paramount importance to military and intelligence operations.

One significant problem with ISAR image formation is the assumption of time invariance of the Doppler frequency used to resolve the image in the cross range. Time variant Doppler becomes present in an ISAR signal when an aircraft is manoeuvring or a ship is pitching and rolling during the coherent processing interval, and is typically referred to as motion error. Using the fast Fourier transform (FT) to cross range focus an image with this motion error present will cause extensive blurring in the cross-range and leave the image unrecognizable even to the most experienced ISAR operators [2-3].

One proven method of motion compensation is the adaptive joint time-frequency (AJTF) algorithm [2-3]. The existing Adaptive Joint Time Frequency (AJTF) based motion compensation technique performs Doppler tracking to individual scatterers via an AJTF projection technique. After maximizing the projection of the phase function to a set of basis functions in the time-frequency plane, the Doppler frequency drift of the strongest scatterer in the range bin is automatically tracked out and the multiple Prominent Point Processing (PPP) scheme is implemented to eliminate both the translational motion error and rotational motion non-uniformity [2-3]. However, this algorithm is not without significant weaknesses of its own. One of the problems is that the computational burden of the exhaustive search used to extract the motion compensation parameters is quite large, which limits its usefulness in an operational situation. Other promising alternatives for the motion compensation are techniques that are based on time-frequency analysis methods [4-6].

A new method is developed in this report to perform target translational and rotational motion non-uniformity compensation for ISAR imaging. The method is based on a registration-restoration-fusion technique. This report contributes another new approach to focus distorted ISAR images and contributes analysis that should add in developing a better picture of the motion compensation in ISAR ima-

ging. The proposed approach has been successfully applied to both experimental and simulated ISAR data.

# 2 Registration-Restoration-Fusion Motion Compensation Procedure

The image registration, restoration and fusion are the basic image processing operations in remote sensing. A recorded image is likely to be degraded by sensor sampling. The purpose of this kind of image processing technique is to operate on the degraded image to obtain an improved image. Since it is similar to ISAR motion compensation, new registration, restoration, and fusion techniques that are suitable for ISAR motion compensation have been developed and integrated into one toolbox to make this motion compensation operation flexible and convenient. The motion compensation process includes three main steps: registration, restoration, and fusion [7-9].

2.1 Image Registration

The image registration is the process of matching two images (reference and input images) so that corresponding coordinate points in the two images refer to the same physical region of the scene being imaged. The accurate sub-pixel registration between two ISAR imaging frames is key to the success of motion compensation. To perform point scatter registration, a method named the 'nearest neighbor method' is developed to search for corresponding control points from two candidate images [7-8]. The method is to set a window around the position of a point scatterer that is found in the reference image. The position of point scatterers in the input image is determined on the chosen window. The registration parameters (scale and rotation angle) can be determined by the position relationship of two sets of control points. Then the registration methods, including the second, third, and fourth order polynomial methods, the linear conformal method, the affine method, and the projective and piecewise linear methods, are investigated and compared to generate the registered image [7-9]. A minimum number of control points are needed for these registration methods. For example, six point scatterers are needed for the second order polynomial method and three point scatterers for the affine registration method. The second order polynomial method is used in this report.

2.2 Blur Estimation and Restoration

The blur estimation is a key step for image restoration. It takes an image that has been degraded by linear blur, which is an image that has been convolved with some

Figure 1: The concept of image fusion.

point-spread function (PSF), and returns an estimate of the original image [10-11]. The PSF can be specified as a mask whose dimensions are smaller than those of the image, or it can be specified as a mask whose dimensions are identical to those of the image. The toolbox provides automatic blur estimation, which can be accessed from the restoration toolbox interface. If the blur function exists, it could be used in the restoration operation directly.

The restoration process can be used after the registration process to reduce blur. It can also be used before the registration to separate two adjacent point scatterers in order to generate accurate motion parameters. Five restoration methods have been evaluated in this study: least squares restoration, resolution-to-noise trade-off restoration, Lucy-Richardson restoration, regularized filter algorithm, and Wiener filter algorithm [12-13]. The Lucy-Richardson restoration method has been used in this report.

2.3 Fusion

Finally, the fusion process is applied to two or more registered ISAR images in order to improve the reliability and capability of target recognition [5-6]. The reason for this is that the fused image has more complete target information than the input images. The fused image is produced from two or more input images by utilizing redundant and complementary information as shown in Figure 1.

It should be emphasized here that there are several methods that have been developed for registration, restoration, and fusion in image processing. It is not the objective of this report to perform trade-off studies of the individual methods. Rather, the objective is to demonstrate the proposed approach by using the experimental and simulated ISAR data and provide some insight as to how the registration-restoration-fusion approach can be used for focusing ISAR images. This report develops the preliminary ground work for this challenging field of research.

3 Results

We demonstrate the application and effectiveness of the registration-restoration-fusion motion compensation method with simulated and measured experimental radar data.

3.1 Simulated Data

To gain a better physical insight into the scattering phenomenon of an aircraft's ISAR image, an aircraft can be assumed to be composed of a set of point scatterers on a two-dimensional plane. Each scattering point on the aircraft does not represent any geometric point on the target but rather a combination of scattering sources that return a radar echo. A two-dimensional model of an aircraft's scattering centres is sufficiently adequate to analyze the ISAR images of aircraft.

In this simulation it is assumed that the target contains six microwave corner reflectors (i.e., scatterers) to simulate the distorting effect that could occur in ISAR images. A picture of the target is shown in Figure 2. The center frequency of the radar is 9 GHz and the bandwidth is 300 MHz. A total of 30 range cells and 50 cross-range cells are used for the imaging. Figure 3a shows the image from the simulated data, without any added motion error, as a reference for comparison. This figure illustrates the undistorted ISAR image when the target is uniformly rotating at a constant rate of 3 degrees/second. Since there are no random motions, we can use the conventional Fourier transform (FT). That is, we take a series of one-dimensional Fourier transforms across the target. As expected, the image is well-focused.

Then perturbed random motion (or motion error) is injected into the simulation. That is, in addition to the uniform (3 degrees/second) rotation perturbed random motion through a 'sine-drive' is injected by adding an additional sine wave to the motion. The resultant rotational motion will then be non-uniform. It should be noted here that the rotational motion of the target is confined to a two-dimensional plane during the coherent processing interval. Figures 3b illustrates the distorted image obtained by using the conventional Fourier transform. In this case, the perturbed oscillation is 1 Hz. The figure clearly shows that the image is severely distorted, which means that the target image itself contains much rotational error. The image is smeared along the cross-range direction. This is because of the target's complex motion due to perturbed random motion during the entire coherent processing interval. The conventional radar imaging that uses the Fourier transform,

Figure 2: *A picture of the simulated target consisting of six simulated corner reflectors.*

Figure 3: *(a) ISAR image using FT. The 6 reflectors are uniformly rotating at a constant rate of 3 degrees/second. The data has no random error. This image is used as a reference for comparison; (b) Distorted ISAR image using FT. The data has random motion error; (c) Distorted ISAR image using FT. The data has random motion error.*

Figure 4: Focused ISAR image using the registration-fusion motion compensation algorithm. (a) Motion compensated image of the data in Figure 4(b) and (b) Motion compensated image of the data in Figure 4(c).

which works well for uniform rotational motion, cannot be directly applied to the perturbed target.

The registration-restoration-fusion method is then applied to these data. Figure 4a illustrates the final image after the registration, restoration, and fusion procedures. All the scatterers are well focused in their individual range and cross-range cells. This implies that all the quadratic phase terms are eliminated.

Figure 3c illustrates another example of a distorted image due to perturbed random motion error. The image is poorly focused and the image of each scatterer is severely smeared. In this case, the perturbed oscillation is 0.57 Hz. Figure 4b shows that the registration-restoration-fusion motion compensation method successfully eliminates the quadratic phase terms and shows a well-focused ISAR image. In Figure 3a, the image from the simulated data without any added motion errors is shown as a reference for comparison. We can see that the motion-compensated image achieves the same sharpness as the reference image.

Another example is a simulated MIG25 aircraft. The radar centre frequency is 9 GHz and the bandwidth is 500 MHz. A total of 64 range cells and 256 cross-range cells are used for the imaging. The FT-based image of the radar target is depicted in Figure 5a. The radar image obtained by using the registration-restoration-fusion

Figure 5: *(a) FT-based ISAR image formation and (b) Registration-restoration-fusion based ISAR image formation.*

approach is presented in Figure 5b. These results suggest that improvement of the radar image can be achieved by using the registration-restoration-fusion approach.

3.2 Experimental Data

A 5m by 5m delta-wing apparatus was constructed to simulate a full size target. A picture of the target is shown in Figure 6. Six corner reflectors were mounted on the apparatus to simulate the major scattering centres of the target. These six corner reflectors were set to oscillate on their own at a controlled rate to simulate the fluttering effect from aircraft parts or mounted stores on aircraft. The apparatus was mounted on a rotating table that can produce rotational motions at a controlled rate. These rotational motions were confined to a two-dimensional plane. Therefore, data from this pseudo point-source target permits an easier and a more definitive analysis of the residual motion effects on ISAR images.

In this section, a set of real data is used to demonstrate the effectiveness of the registration-restoration-fusion motion compensation procedure. This experimental data set is particularly useful since the entire data set consists of 60,000 pulses in the cross-range. The data covers 30 seconds for which one second of data corresponds to 2000 samples in the cross-range. Therefore 30 seconds of data corresponds to 60000 samples in the cross-range. There are 41 down range bins. The 60,000 pulses can be cut into different size imaging intervals with each of these intervals displaying a different amount of error.

The images shown in the examples are from the time-frequency based imaging. The image at the time of the first, second, and third second are taken to demonstrate the motion compensation process described in the previous section. The results are shown in Figure 7. In this figure, the image at the time of the first second in Figure 7a is a reference image. The image at the time of the third second in Figure

Table 1: The position of the point scatterers in the reference image, input image, and registered image.

Reference Image (Base Points)		Input Image (Input Points)		Registered Image	
25	11	24	9	25	11
17	24	17	26	17	24
26	21	26	20	26	21
27	30	27	31	27	30
23	29	23	29	23	29
21	18	21	18	21	18

Figure 6: A picture of the target motion simulator experimental apparatus.

Figure 7: *The results from frame 12 and 13 of real data. (a) Reference image; (b) input image; (c) registered image; (4) fused image.*

Figure 8: *The results from frame 1 and 3 of real data. (a) Reference image; (b) input image; (c) registered image; (4) fused image.*

**Table 2:** *The position of the point scatterers in the reference image, input image, and registered image.*

Reference Image (Base Points)		Input Image (Input Points)		Registered Image	
25	24	25	26	25	24
28	23	28	24	28	23
25	20	25	19	25	20
20	21	20	21	20	21
21	18	21	16	21	18
19	25	19	27	19	25

7b is the input image and will be registered to the reference image. The image in Figure 7c is the registration result. The corresponding positions of control points and the positions of point scatterers of the registered image are shown in Table 1. The result shows that the registration method gives good performance. The fused image is shown in Figure 7d.

Figure 8 shows the results of a second example corresponding to the 12th and the 13th second of the data. The 12th second image in Figure 8a is considered as the reference image, and the 13th second image in Figure 8b is the input image that is registered to the reference image. The result is shown in Figure 8c, and the corresponding positions of the point scatterers are shown in Table 2. The processing also gives good performance. The fused image is shown in Figure 8d and is more focused than the original image.

4 Conclusion

A motion compensation method based on a registration-restoration-fusion image processing approach has been proposed to perform ISAR motion compensation. The registration-restoration-fusion motion compensation method has been applied to the simulated and measured experimental ISAR data sets. The results demonstrate that the registration-restoration-fusion motion compensation approach gives good performance and generates focused ISAR images. In the future, the registration-restoration-fusion-based motion compensation method could be used to estimate parameters of motion, and the estimated parameters could be applied to multiple prominent point-processing models. This report provides the preliminary ground work for this challenging field of research.

Results also show that if a target is moving smoothly, standard motion compensation generates a clear image of the target by using the conventional Fourier transform methods. However, when a target performs complex motion such as perturbed random motions, standard motion compensation is not sufficient to generate an acceptable image. In this case, the registration-restoration-fusion motion compensation method provides an efficient candidate to resolve the image smearing caused by the time-varying behavior and leads to a well-focused ISAR image. This study also adds insight into the distortion mechanisms that affect the ISAR images of a target in motion.

Acknowledgments

References

1. C. C. Chen and H. C. Andrews, Target motion induced radar imaging, IEEE Trans. Aerosp. Electron. Syst., 16, pp. 2–14, 1980.

2. Y. X. Wang, L. Hao, and Chen C.C., ISAR motion compensation via adaptive joint time-frequency technique, IEEE Trans. On Aerosp. Electron. Syst., vol. 34, No. 2, April 1998.

3. T. Thayaparan, G. Lampropoulos, S.K. Wong and E. Riseborough, Application of an adaptive joint time-frequency algorithm for focusing distorted ISAR images from simulated and measured radar data, IEE Proceedings – Radar, Sonar and Navigation, Volume: 150, Issue: 4, Aug. 2003.

4. V. C. Chen and H. Ling, Time-Frequency Transforms for Radar Imaging and Signal Analysis, Artech House, Boston, MA, USA, 2002.

5. G. Lampropoulos, T. Thayaparan, and N. Xie, Fusion of Time Frequency Distributions and Applications to Radar Signals, Journal of Electronic Imaging, in press, 2006.

6. T. Thayaparan, and G. Lampropoulos (2003). A new approach in time-frequency analysis with applications to experimental high resolution radar, DRDC Ottawa TR 2003-187, Defence R&D Canada - Ottawa.

7. B. Zitova and J. Flusser, Image registration methods: a survey, Image and Vision Computing, 21, pp. 977-1000, 2003.

8. T. M. Lehmann, C. Gonner, and K. Spitzer, Survey: interpolation methods in medical image processing, IEEE Trans. on Medical Imaging, Vol. 18, No. 11, pp. 1049-1075, 1999.

9. G. Lampropoulos, Radar image enhancement, feature extraction and motion compensation using time-frequency and time-scale techniques, A.U.G. Signals, Toronto, 2004.

10. J. H. Elder and S. W. Zucker, Local scale control for edge detection and blur estimation, IEEE Trans. on Pattern and Analysis and Machine Intelligence, Vol. 20, No. 7, pp. 699-715, July 1998.

11. Grinvald, A., Lieke, E. E., Frostig, R. D., and Hildesheim, R. (1994). Cortical point-spread function and long-range lateral interactions revealed by real-time

optical imaging of macaque monkey primary visual cortex. Journal of Neuroscience, 14:2545– 2568.

12. W. H. Richardson, "Bayesian-based iterative method of image restoration," J. Opt. Soc. Am., vol. 62, pp. 55–59, 1972.

13. L. B. Lucy. An iterative technique for the rectification of observed distributions. The Astronomical Journal, 79(6):745–754, 1974.

14. R. C. Gonzalez and P. Winttz, Digital Image Processing, Addison Wesley, Reading, MA, 1997.

15. O. Rockinger, Pixel-level fusion of image sequences using wavelet frames, Proceedings of the 16th Leeds Applied Shape Research Workshop, Leeds University Press, 1996.

DOCUMENT CONTROL DATA
(Security classification of title, body of abstract and indexing annotation must be entered when the overall document is classified)

1. ORIGINATOR (the name and address of the organization preparing the document. Organizations for whom the document was prepared, e.g. Establishment sponsoring a contractor's report, or tasking agency, are entered in section 8.) Defence R&D Canada – Ottawa Ottawa, Ontario, Canada K1A 0Z4	2. SECURITY CLASSIFICATION (overall security classification of the document, including special warning terms if applicable) UNCLASSIFIED

3. TITLE (the complete document title as indicated on the title page. Its classification should be indicated by the appropriate abbreviation (S,C or U) in parentheses after the title.)

    ISAR Motion Compensation using the registration-restoration-fusion method (U)

4. AUTHORS (Last name, first name, middle initial)

    Thayaparan, Thayananthan

5. DATE OF PUBLICATION (month and year of publication of document) June 2006	6a. NO. OF PAGES (total containing information. Include Annexes, Appendices, etc.) 27	6b. NO. OF REFS (total cited in document) 15

7. DESCRIPTIVE NOTES (the category of the document, e.g. technical report, technical note or memorandum. If appropriate, enter the type of report, e.g. interim, progress, summary, annual or final. Give the inclusive dates when a specific reporting period is covered.)

    DRDC Ottawa Technical Memorandum

8. SPONSORING ACTIVITY (the name of the department project office or laboratory sponsoring the research and development. Include the address.)

    Defence R&D Canada – Ottawa
    Ottawa, Ontario, Canada K1A 0Z4

9a. PROJECT OR GRANT NO. (if appropriate, the applicable research and development project or grant number under which the document was written. Please specify whether project or grant) 13ec05	9b. CONTRACT NO. (if appropriate, the applicable number under which the document was written)
10a. ORIGINATOR'S DOCUMENT NUMBER (the official document number by which the document is identified by the originating activity. This number must be unique to this document.) DRDC Ottawa TM 2006-131	10b. OTHER DOCUMENT NOS. (Any other numbers which may be assigned this document either by the originator or by the sponsor)

11. DOCUMENT AVAILABILITY (any limitations on further dissemination of the document, other than those imposed by security classification)

    (X) Unlimited distribution
    ( ) Distribution limited to defence departments and defence contractors; further distribution only as approved
    ( ) Distribution limited to defence departments and Canadian defence contractors; further distribution only as approved
    ( ) Distribution limited to government departments and agencies; further distribution only as approved
    ( ) Distribution limited to defence departments; further distribution only as approved
    ( ) Other (please specify):

12. DOCUMENT ANNOUNCEMENT (any limitation to the bibliographic announcement of this document. This will normally correspond to the Document Availability (11). However, where further distribution (beyond the audience specified in 11) is possible, a wider announcement audience may be selected.)

13. ABSTRACT (a brief and factual summary of the document. It may also appear elsewhere in the body of the document itself. It is highly desirable that the abstract of classified documents be unclassified. Each paragraph of the abstract shall begin with an indication of the security classification of the information in the paragraph (unless the document itself is unclassified) represented as (S), (C), or (U). It is not necessary to include here abstracts in both official languages unless the text is bilingual).

(U) A new method is developed to perform target translational and rotational motion compensation for ISAR imaging. The method is based on a registration-restoration-fusion technique. The basic idea is to use the nearest neighbor method to obtain control points and estimate motion parameters from two or more candidate images. The registration processes use these estimated motion parameters to remove both translational and rotational motion. The restoration process may be used to eliminate the blur that is induced by the registration process. Furthermore, the fusion of two registered images before or after restoration processing could be used to generate the focused ISAR image. This proposed method has been successfully applied to both experimental and simulated ISAR data.

14. KEYWORDS, DESCRIPTORS or IDENTIFIERS (technically meaningful terms or short phrases that characterize a document and could be helpful in cataloguing the document. They should be selected so that no security classification is required. Identifiers such as equipment model designation, trade name, military project code name, geographic location may also be included. If possible keywords should be selected from a published thesaurus. e.g. Thesaurus of Engineering and Scientific Terms (TEST) and that thesaurus-identified. If it is not possible to select indexing terms which are Unclassified, the classification of each should be indicated as with the title.)

SAR
ISAR
Registration
Time-Frequency Analysis
Restoration
Fusion
Target Detection
Fourier Transform
Doppler Processing
Image Analysis

Defence R&D Canada

Canada's Leader in Defence
and National Security
Science and Technology

R & D pour la défense Canada

Chef de file au Canada en matière
de science et de technologie pour
la défense et la sécurité nationale

DEFENCE **R&D** DÉFENSE

www.drdc-rddc.gc.ca